Package 'amregtest'

August 4, 2026

Title Runs Allelematch Regression Tests

Version 1.3.2

Date 2026-08-04

Description Automates regression testing of package 'allelematch'. Over 2500 tests cover all functions in 'allelematch', reproduce the examples from the documentation, and include negative tests. The implementation is based on 'testthat'.

License MIT + file LICENSE

URL https://github.com/torstax/amregtest

BugReports https://github.com/torstax/amregtest/issues

Depends R (>= 3.5)

Imports digest, R6, remotes, testthat (>= 3.0.0), utils, withr

Suggests allelematch, rstudioapi

Config/testthat/edition 3

Encoding UTF-8

Language en-US

LazyData true

Config/roxygen2/markdown TRUE

Config/roxygen2/version 8.0.0

NeedsCompilation no

Author Department of Wildlife, Fish and Environmental Studies at Swedish University of Agricultural Sciences [cph],
Göran Spong [cph] (Senior Lecturer at the Department of Wildlife, Fish and Environmental Studies),
Paul Galpern [ctb] (Author of the excellent package 'allelematch' from which the five amExample data files have been copied under MIT license),
Torvald Staxler [aut, cre]

Maintainer Torvald Staxler <torvald.staxler@telia.com>

Repository CRAN

Date/Publication 2026-08-04 21:40:18 UTC

Contents

amExample1 . . . 2
amExample2 . . . 3
amExample3 . . . 3
amExample4 . . . 4
amExample5 . . . 4
amregtest . . . 5
artData . . . 5
artInstallCranAllelematch . . . 6
artList . . . 7
artRun . . . 8
artVersion . . . 9

Index **11**

`amExample1` *Example 1 High quality data set*

Description

This is sample data copied from amExampleData in version 5.2.1 of package allelematch.

Format

Data frame with samples in rows, and alleles in columns. Missing data is represented as "-99".

Details

The data in this example is simulated to represent a high quality data set that might result from a laboratory protocol where samples were run multiple times to confirm their identity. It has no genotyping error, a near-zero missing data load, and approximately 60% of the individuals have been artificially resampled more than once.

References

https://github.com/cran/allelematch

amExample2 *Example 2 Good quality data set*

Description

This is sample data copied from amExampleData in version 5.2.1 of package allelematch.

Format

Data frame with samples in rows, and alleles in columns. Missing data is represented as "-99".

Details

The data in this example have also been simulated, this time to reflect the qualities of good quality data set, where genotyping error and missing data exist, but these can be confidently handled by allelematch without manual intervention. At each locus a random 4% of heterozygotes lost their second allele to simulate an allele dropout, and a random 4% of samples at each locus had alleles set to missing.

References

https://github.com/cran/allelematch

amExample3 *Example 3 Marginal quality data set*

Description

This is sample data copied from amExampleData in version 5.2.1 of package allelematch.

Format

Data frame with samples in rows, and alleles in columns. Missing data is represented as "-99".

Details

The data in this example have been simulated to represent a data set of marginal quality where the use of allelematch combined with careful manual review of the results is required to achieve a confident assessment of the unique genotypes. At each locus a random 4% of heterozygotes lost their second allele to simulate an allele dropout, and a random 10% of samples at each locus had alleles set to missing.

References

https://github.com/cran/allelematch

---

amExample4 *Example 4 Low quality data set*

Description

This is sample data copied from amExampleData in version 5.2.1 of package allelematch.

Format

Data frame with samples in rows, and alleles in columns. Missing data is represented as "-99".

Details

For this example we have simulated a low quality data set where uncertainty created by genotyping error and missing data, combined with a lack of information in the form of allelic diversity across loci will result in a low confidence assessment of the unique genotypes. At each locus a random 6% of heterozygotes lost their second allele to simulate an allele dropout, and a random 20% of samples at each locus had alleles set to missing.

References

https://github.com/cran/allelematch

---

amExample5 *Example 5 Wildlife data set*

Description

This is sample data copied from amExampleData in version 5.2.1 of package allelematch.

Format

Data frame with samples in rows, and alleles in columns. Missing data is represented as "-99".

Details

In this final example we use real data from the non-invasive sampling of a wildlife population. The data have been anonymized by changing sampling details. A single column giving the gender is also available and we show how this can be used as an extra locus. Missing data is also more common at some loci than at others, with a total load of about 10%.

References

https://github.com/cran/allelematch

`amregtest` *Package Overview*

Description

Package 'amregtest' automates regression testing of package allelematch.

The API is simple. There are only four functions:

`artRun()`	Executes the test, or a subset of the tests
`artList()`	Lists the available tests without running them
`artVersion()`	Shows the used versions of 'allelematch' and 'amregtest'
`artInstallCranAllelematch()`	Installs official CRAN version of 'allelematch'

The prefix "art" is short for "Allelematch Regression Test".

See artData for a description of data sets used as input.

References

https://github.com/cran/allelematch

allelematchSuppDoc.pdf

`artData` *Example data used by amregtest*

Description

This example data is used when testing allelematch backwards compatibility using artRun. The tests load this data and passes it to amDataset.

It includes data that was imported from version 5.2.1 of allelematch. It was still unchanged in 5.2.5.

amExample1	Example 1 High quality data set
amExample2	Example 2 Good quality data set
amExample3	Example 3 Marginal quality data set
amExample4	Example 4 Low quality data set
amExample5	Example 5 Wildlife data set

See allelematchSuppDoc.pdf for a more detailed description.

It also includes a large data set gathered from field work:

ggSample	Very large wildlife data set

Format

Data frames with varying numbers of samples in rows, and alleles in columns. Missing data is represented as "-99".

References

https://github.com/cran/allelematch

allelematchSuppDoc.pdf

`artInstallCranAllelematch` *Installs official version of 'allelematch' from CRAN.*

Description

This is a convenience function that installs one of the official version of 'allelematch' from CRAN.

It calls `remotes::install_version()` to install the specified version.

If executed from a RStudio Console, it then calls `rstudioapi::restartSession()` to ensure that the installed version of 'allelematch' is also the loaded version in the current R session.

Note that the CRAN version will be built from source code at installation. This means that artVersion will show a "(Built HH:MM)" timestamp from the installation rather than from when it was published on CRAN.

Usage

```
artInstallCranAllelematch(version = "3.0.0")
```

Arguments

`version`	string. Default "3.0.0".

See Also

artVersion, artList, artRun and amregtest

Examples

```
# Install the default official versions of 'allelematch' from CRAN:
artInstallCranAllelematch()

# Install another official version of 'allelematch' from CRAN:
artInstallCranAllelematch("2.5.3")
```

`artList` *Lists available tests in* `amregtest` *without running them*

Description

Use the output to select a value for parameter `filter` to artRun. Useful when debugging.

Usage

```
artList(verbose = TRUE)
```

Arguments

`verbose`	logical. If TRUE (the default), prints additional info to stdout

Value

A character vector containing the names of all the tests

See Also

artVersion, artRun, artInstallCranAllelematch and amregtest

Examples

```
# See what version of packages 'allelematch' and 'amregtest'
# are currently loaded:
artVersion()

# List the available tests:
artList()

# Run all the tests:
# artRun()  # Takes several minutes

# Run the first of the available tests:
artRun(filter="allelematch_1-amDataset$")
```

`artRun` *Runs the regression test*

Description

Runs regression tests on package allelematch to make sure it is backwards compatible.

The full set of tests will take a couple of minutes.

Call artList to see the available tests without running them.

Usage

```
artRun(filter = "", verbose = TRUE, keep = FALSE)
```

Arguments

`filter`	If specified, only tests with names matching this perl regular expression will be executed. Character vector of length 1. See also artList
`verbose`	logical. If TRUE (the default), prints version of tested allelematch to stdout
`keep`	logical. If FALSE (the default), deletes the temporary files created by the tests. This includes .htm and .png files for browsers and Viewer. If TRUE, keeps the temporary files for inspection.

Details

If any of the test executed with artRun should fail, then we want to be able to run that specific test under the debugger.

Set a breakpoint in `allelematch.R` and call `artRun(filter="<the test that reproduces the problem>")`

Note that it is the last loaded version of `allelematch` that will be executed, not the last edited. In RStudio, CTRL+SHIFT+B will build, install and load.

Value

A list (invisibly) containing data about the test results as returned by test_package

See Also

artVersion, artList, artInstallCranAllelematch and amregtest

Examples

```
# See what version of packages 'allelematch' and 'amregtest'
# are currently loaded:
artVersion()

# List the available tests:
artList()

# Run all the tests:
# artRun()  # Takes several minutes

# Run the first of the available tests:
artRun(filter="allelematch_1-amDataset$")
```

`artVersion` *Returns package version*

Description

Displays version of this package (amregtest) and of allelematch, together with build timestamps.

The version is specified in the file DESCRIPTION, tag "Version: ".

If allelematch was installed with artInstallCranAllelematch it will show a build timestamp from the installation, not from when it was published.

Usage

```
artVersion(verbose = TRUE)
```

Arguments

`verbose`	logical. If TRUE (the default), prints additional info to stdout, including versions and build timestamps of 'allelematch' and 'amregtest'.

Value

The loaded version of this package (amregtest-package) in a character vector of length one

See Also

artList, artRun, artInstallCranAllelematch and amregtest

Examples

```
# See what version of packages 'allelematch' and 'amregtest'
# are currently loaded:
artVersion()

# List the available tests:
artList()

# Run all the tests:
# artRun()  # Takes several minutes

# Run the first of the available tests:
artRun(filter="allelematch_1-amDataset$")
```

Index

∗ **data**
amExample1, 2
amExample2, 3
amExample3, 3
amExample4, 4
amExample5, 4
artData, 5

allelematch, *2–5*, *8, 9*
amDataset, *5*
amExample1, 2, *5*
amExample2, 3, *5*
amExample3, 3, *5*
amExample4, 4, *5*
amExample5, 4, *5*
amExampleData, *2–4*
amregtest, *5*, 5, *6–9*
amregtest-package, *9*
artData, *5*, 5
artInstallCranAllelematch, *5*, 6, *7–9*
artList, *5, 6*, 7, *8, 9*
artRun, *5–8*, 8, *9*
artVersion, *5–8*, 9

ggSample, *6*

remotes::install_version(), *6*
rstudioapi::restartSession(), *6*

test_package, *8*